

SS.SEB



LOAD ANGLE CHART 吊装角度表

α max / 最大 : 90° / β max / 最大 : 60°
L : Load / 载荷

4:1

max. load in t
最大载荷 (吨)

METRIC THREADS / 公制螺纹	Torque / 扭矩 (Nm)										
Number of rings / 吊环数量		1	2	1	2	2			3 → 4		
Lifting angle β / 吊装角度 (β)		0°	0°	0°	0°	0° → 45°	45° → 60°	Asymmetric / 非对称	0° → 45°	45° → 60°	Asymmetric / 非对称
Loading angle α / 受载角度 (α)		0°	0°	90°	90°	0° → 45°	45° → 60°		0° → 45°	45° → 60°	
SS.SEB M 8	6	0,40	0,80	0,20	0,40	0,28	0,20	0,20	0,42	0,20	0,20
SS.SEB M 10	10	0,60	1,20	0,30	0,60	0,42	0,30	0,30	0,63	0,30	0,30
SS.SEB M 12 0,4t	15	0,80	1,60	0,40	0,80	0,56	0,40	0,40	0,84	0,40	0,40
SS.SEB M 12	15	0,55	1,10	0,55	1,10	0,77	0,55	0,55	1,15	0,83	0,55
SS.SEB M 16	50	1,20	2,40	1,20	2,40	1,68	1,20	1,20	2,52	1,80	1,20
SS.SEB M 20	100	1,50	3,00	1,50	3,00	2,10	1,50	1,50	3,15	2,25	1,50
SS.SEB M 24	100	2,50	5,00	2,50	5,00	3,50	2,50	2,50	5,25	3,75	2,50

4:1

max. load in lbs
最大载荷 (磅)

UNC THREADS / 美制统一粗牙螺纹	Torque / 扭矩 (ft-lb)										
Number of rings / 吊环数量		1	2	1	2	2			3 → 4		
Lifting angle β / 吊装角度 (β)		0°	0°	0°	0°	0° → 45°	45° → 60°	Asymmetric / 非对称	0° → 45°	45° → 60°	Asymmetric / 非对称
Loading angle α / 受载角度 (α)		0°	0°	90°	90°	0° → 45°	45° → 60°		0° → 45°	45° → 60°	
SS.SEB U 038	8	1,100	2,200	550	1,100	770	550	550	1,155	550	550
SS.SEB U 050	12	1,760	3,520	880	1,760	1,232	880	880	1,848	880	880

SS.SEB



LOAD ANGLE CHART 吊装角度表

α max / 最大 : 90° / β max / 最大 : 60°
L : Load / 载荷

5:1

max. load in t
最大载荷 (吨)

METRIC THREADS / 公制螺纹	Torque / 扭矩 (Nm)										
Number of rings / 吊环数量		1	2	1	2	2			3 → 4		
Lifting angle β / 吊装角度 (β)		0°	0°	0°	0°	0° → 45°	45° → 60°	Asymmetric / 非对称	0° → 45°	45° → 60°	Asymmetric / 非对称
Loading angle α / 受载角度 (α)		0°	0°	90°	90°	0° → 45°	45° → 60°		0° → 45°	45° → 60°	
SS.SEB M 8	6	0,40	0,80	0,20	0,40	0,28	0,20	0,20	0,42	0,20	0,20
SS.SEB M 10	10	0,60	1,20	0,30	0,60	0,42	0,30	0,30	0,63	0,30	0,30
SS.SEB M 12 0,4t	15	0,80	1,60	0,40	0,80	0,56	0,40	0,40	0,84	0,40	0,40
SS.SEB M 12	15	0,55	1,10	0,55	1,10	0,77	0,55	0,55	1,15	0,83	0,55
SS.SEB M 16	50	1,20	2,40	1,20	2,40	1,68	1,20	1,20	2,52	1,80	1,20
SS.SEB M 20	100	1,50	3,00	1,50	3,00	2,10	1,50	1,50	3,15	2,25	1,50
SS.SEB M 24	100	2,50	5,00	2,50	5,00	3,50	2,50	2,50	5,25	3,75	2,50

5:1

max. load in lbs
最大载荷 (磅)

UNC THREADS / 美制统一粗牙螺纹	Torque / 扭矩 (ft-lb)										
Number of rings / 吊环数量		1	2	1	2	2			3 → 4		
Lifting angle β / 吊装角度(β)		0°	0°	0°	0°	0° → 45°	45° → 60°	Asymmetric / 非对称	0° → 45°	45° → 60°	Asymmetric / 非对称
Loading angle α / 受载角度(α)		0°	0°	90°	90°	0° → 45°	45° → 60°		0° → 45°	45° → 60°	
SS.SEB U 038	8	1,100	2,200	550	1,100	770	550	550	1,155	550	550
SS.SEB U 050	12	1,760	3,520	880	1,760	1,232	880	880	1,848	880	880