



1 in = 25.4 mm

| Reference | Diameter | SF 5:1 WLL (t) | SF 4:1 WLL (t) | L Maxi (mm) | Torque (Nm) | S (mm) | A (mm) | B (mm) | C (mm) | D (mm) | E (mm) | F (mm) | G (mm) | H (mm) | Weight (kg) |
|----------------|--------------|----------------|----------------|-------------|-------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|-------------|
| SS.FE.DSR M 8 | M 8 (x1,25) | 0,30 | 0,30 | 43 | 6 | 20 | 43 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 0,9 |
| SS.FE.DSR M 10 | M 10 (x1,50) | 0,50 | 0,50 | 43 | 10 | 20 | 43 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 0,9 |
| SS.FE.DSR M 12 | M 12 (x1,75) | 0,80 | 0,80 | 43 | 15 | 20 | 43 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 0,9 |
| SS.FE.DSR M 14 | M 14 (x2) | 1,00 | 1,00 | 43 | 30 | 20 | 43 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 0,9 |
| SS.FE.DSR M 16 | M 16 (x2) | 1,40 | 1,50 | 43 | 50 | 20 | 43 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 0,9 |
| SS.FE.DSR M 18 | M 18 (x2,5) | 1,40 | 1,50 | 62 | 70 | 24 | 62 | 55 | 58 | 83 | 56 | 25 | 115 | 19 | 2,6 |
| SS.FE.DSR M 20 | M 20 (x2,5) | 1,40 | 1,60 | 62 | 100 | 24 | 62 | 55 | 58 | 83 | 56 | 25 | 115 | 19 | 2,6 |
| SS.FE.DSR M 22 | M 22 (x2,5) | 2,20 | 2,20 | 62 | 120 | 24 | 62 | 55 | 58 | 83 | 56 | 25 | 115 | 19 | 2,6 |